

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
6 December 2001 (06.12.2001)


PCT

(10) International Publication Number
WO 01/92675 A2

- (51) International Patent Classification⁷: **E21B**
- (21) International Application Number: PCT/US01/17152
- (22) International Filing Date: 25 May 2001 (25.05.2001)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
09/586,648 1 June 2000 (01.06.2000) US
- (71) Applicant: **MARATHON OIL COMPANY** [US/US];
5555 San Felipe, Houston, TX 77056 (US).
- (72) Inventors: **SNIDER, Philip, M.**; 12102 Rocky Lake Drive, Houston, TX 77070 (US). **ZIEROLF, Joseph, A.**; 103 Angelle Circle, Houma, LA 70360 (US).
- (74) Agent: **EBEL, Jack, E.**; 11735 Applewood Knolls Drive, Lakewood, CO 80215 (US).
- (81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZW.
- (84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).
- Published:
— without international search report and to be republished upon receipt of that report

[Continued on next page]

(54) Title: METHOD AND SYSTEM FOR PERFORMING OPERATIONS AND FOR IMPROVING PRODUCTION IN WELLS



(57) Abstract: A method for performing operations and for improving production in a well includes the steps of: providing radio identification devices at known locations in the well, and providing a reader device configured to read the identification devices, and to control the operations responsive to signals from the identification devices. The method also includes the steps of providing a process tool, and transporting the process tool and the reader device through the well. The reader device is programmed to control the process tool upon reception of a response signal from a selected identification device. The method can be used to perform perforating processes, packer setting processes, bridge plug setting processes, logging processes inspection processes, chemical treating processes, and cleaning processes. In addition, the method can be performed dynamically by controlling the tool as it moves through the well, or statically by stopping the tool at a particular location within the well. A system for performing the method includes the identification devices, the reader device, the process tool, and a computer or controller. In addition the identification devices can be placed in casing collars of the well and can be configured as passive devices or as active devices.

WO 01/92675 A2



For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

5

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

APPLICATION FOR LETTERS PATENT

10

15

20

**METHOD AND SYSTEM FOR PERFORMING
OPERATIONS AND FOR IMPROVING
PRODUCTION IN WELLS**

25

30

35

40

ATTORNEY'S DOCKET NO. 200007 USA

Cross Reference to Related Applications

This application is a continuation-in-part of patent application serial no. 09/286,650, filed April 6, 1999, entitled "Method And Apparatus For Determining Position In A Pipe".

5

Field of the Invention

This invention relates to generally to wells used in the production of fluids such as oil and gas. More specifically, this invention relates to a method and system for performing various operations and for improving production in wells.

10

Background of the Invention

Different operations are performed during the drilling and completion of a subterranean well, and also during the production of fluids from subterranean formations via the completed well. For example, different downhole operations are typically performed at some depth within the well, but are controlled at the surface.

15

A perforating process is one type of downhole operation that is used to perforate a well casing. A conventional perforating process is performed by placing a perforating tool (i.e., perforating gun) in a well casing, along a section of the casing proximate to a geological formation of interest. The perforating tool carries shaped charges that are detonated using a signal transmitted from the surface to the charges. Detonation of the charges creates openings in the casing and concrete around the casing, which are then used to establish fluid communication between the geological formation, and the inside diameter of the casing.

20

25

Another example of a downhole operation is the setting of packers within the well casing to isolate a particular section of the well or a particular geological formation. In this case, a packer can be placed within the well casing at a desired depth, and then set by a setting tool actuated from the surface. Other exemplary downhole operations include the placement of logging tools at a particular geological formation or depth within the well casing, and the placement of bridge plugs, casing patches, tubulars, and associated tools in the well casing.

30

35

One critical aspect of any downhole operation involves ascertaining the depth in the well where the operation is to be performed. The depth is typically ascertained using well logs. A conventional well log includes continuous readings from a logging instrument, and an axis which represents the well depths at which the readings were obtained. The instrument readings measure rock characteristics such as natural gamma ray radiation, electrical resistivity, density and acoustic properties. Using these rock characteristics geological formations of interest within the well, such as oil and gas bearing formations, can be identified. The well is initially logged "open hole" which becomes the bench mark for all future logs. After the well is cased, a cased hole log is then prepared and correlated, or "tied in", to the open hole log.

Using the logs and a positioning mechanism, such as a wire line or coiled tubing, coupled to an odometer, a tool can be placed at a desired depth within the well, and then actuated as required to perform the downhole operation. One problem with conventional logging and positioning techniques is that it is difficult to accurately identify the depth of the tool, and to correlate the depth to the open hole logs.

Figure 1 illustrates a prior art perforating process being performed in an oil and gas well 10. The well 10 includes a well bore 12, and a casing 14 within the well bore 12 surrounded by concrete 16. The well 10 extends from an earthen surface 18 through geological formations within the earth, which are represented as Zones A, B and C. The casing 14 is formed by tubular elements, such as pipe or tubing sections, connected to one another by collars 20. In this example the tubular elements that form the casing 14 are about 40 feet long so that the casing collars 20 are forty feet apart. However, tubular elements with shorter lengths (e.g., twenty feet) can be interspersed with the forty feet lengths to aid in depth determinations. Thus in Figure 1 two of the casing collars 20 are only twenty feet apart.

For performing the perforating operation a perforating tool 22 has been lowered into the casing 14 on a wire line 24. A mast 26 and pulleys 28 support the wire line 24, and a wire line unit 30 controls the wire line 24. The wire line unit 30 includes a

drive mechanism 32 that lowers the wire line 24 and the tool 22 into the well 10, and raises the wire line 24 and the tool 22 out of the well 10 at the completion of the process. The wire line unit 30 also includes an odometer 34 that measures the unwound
5 length of the wire line 24 as it is lowered into the well 10, and equates this measurement to the depth of the tool 22 within the well.

During formation of the well 10 an open hole log 36 was prepared. The open hole log 36 includes various instrument
10 readings, such as gamma ray readings 38 and spontaneous potential (SP) readings 40 which are plotted as a function of depth in feet. For simplicity only a portion of the open hole log 36, from about 7000 feet to about 7220 feet, is illustrated. However, in actual practice the entire well 10 from the surface
15 18 to the bottom of the well 10 may be logged. The open hole log 36 permits skilled artisans to ascertain the oil and gas containing formations within the well 10 and the most productive intervals of those formations. For example, based on the gamma ray readings 38 and the SP readings 40 it is determined that Zone
20 A may contain oil and gas reserves. It is thus desired to perforate the casing 14 along a section thereof proximate to Zone A.

In addition to the open hole log 36, following casing of the well 10, cased hole gamma ray readings 44 are made, and a casing
25 collar log 42 can be prepared. The casing collar log 42 is also referred to as a PDC log (perforating depth control log). The casing collar log 42 can be used to identify the section of the casing 14 proximate to Zone A where the perforations are to be made.

30 Using techniques and equipment that are known in the art, the casing collar log 42 can be accurately correlated, or "tied in", to the open hole log 36. However, using conventional positioning mechanisms, such as the wire line unit 30, it may be difficult to accurately place the perforating tool 22 at the required depth
35 within the well. For example, factors such as stretching, elongation from thermal effects, sinusoidal and helical buckling, and deformation of the wire line 24 can affect the odometer readings, and the accuracy of the odometer readings relative to the open hole odometer readings.

Thus, as shown in Figure 1, the odometer readings which indicate the depth of the perforating tool 22, may not equate to the actual depths, as reflected in the open hole log 36 and the casing collar log 42 . In this example, the odometer readings
5 differ from the depths identified in the open hole log 36 and the casing collar log 42 by about 40 feet. With this situation, when the perforating tool 22 is fired, the section of casing 20 proximate to Zone A may be only partially perforated, or not perforated at all.

10 Because of these tool positioning inaccuracies, various correlative joint logging and wire logging techniques have been developed in the art. For example, one prior art technique uses electronic joint sensors, and electrically conductive wire line, to determine joint-to-joint lengths, and to correlate the odometer
15 readings of the wire line to the casing collar log. Although these correlative joint logging and wire line logging techniques are accurate, they are expensive and time consuming. In particular, additional crews and surface equipment are required, and additional wire line footage charges are incurred.

20 In addition to tool positioning inaccuracies, computational errors also introduce inaccuracies in depth computations. For example, a tool operator can make computational errors by thinking one number (e.g., 7100), while the true number may be different (e.g., 7010). Also, the tool operator may position the
25 tool by compensating a desired amount in the uphole direction, when in reality the downhole direction should have been used. These computational errors are compounded by fatigue, the weather, and communication problems at the well site.

It would be desirable to obtain accurate depth readings for
30 downhole tools without the necessity for complicated and expensive correlative joint logging and wire logging techniques. In addition, it would be desirable to control down hole operations and processes without having to rely on inaccurate depth readings contaminated by computational errors. The present invention is
35 directed to an improved method and system for performing operations and processes in wells, in which the depths of down hole tools are accurately ascertained and used to control the operations and processes.

Another limitation of conventional downhole operations that are dependent on depth measurements, is that downhole tools must first be positioned in the well, and then actuated from the surface. This requires additional time and effort from well
5 crews. In addition, surface actuation introduces additional equipment and variables to the operations. It would be advantageous to be able to control downhole operations without the requirement of surface actuation of the downhole tools. With the present invention actuation of downhole tools can be
10 performed in the well at the required depth.

Summary of the Invention

In accordance with the present invention a method and a system for performing various operations in wells, and for
15 improving production in wells, are provided. Exemplary operations that can be performed using the method include perforating processes, packer setting processes, bridge plug setting processes, logging processes, inspection processes, chemical treating processes, casing patch processes, jet cutting
20 processes and cleaning processes. Each of these processes, when performed in a well according to the method, improves the well and improves production from the well.

In an illustrative embodiment the method is used to perform a perforating process in an oil or gas production well. The well
25 includes a well bore, and a well casing, extending from an earthen or subsea surface into various geological zones within the earth. The well casing includes lengths of pipe or tubing joined together by casing collars.

The method includes the initial step of providing
30 identification devices at spaced intervals along the length of the well casing. The identification devices can comprise active or passive radio identification devices installed in each casing collar of the well casing. Each radio identification device is uniquely identified, and its depth, or location, within the well is
35 accurately ascertained by correlation to well logs. Similarly, each casing collar is uniquely identified by the radio identification device contained therein, and a record of the well

including the depth of each casing collar and identification device is established.

The method also includes the step of providing a reader device, and a transport mechanism for moving the reader device
5 through the well casing proximate to the identification devices. In the illustrative embodiment the reader device comprises a radio frequency transmitter and receiver configured to provide transmission signals for reception by the identification devices. The identification devices are configured to receive the
10 transmission signals, and to transmit response signals back to the reader device. The transport mechanism for the reader device can comprise a wire line, tubulars, coil tubing, a robotic mechanism, a fluid transport mechanism such as a pump or a blower, a free fall arrangement, or a controlled fall arrangement
15 such as a parachute.

In addition to transmitting and receiving signals from the identification devices, the reader device is also configured to transmit control signals for controlling a process tool, as a function of the response signals from the identification devices.
20 For example, the reader device can control a perforating tool configured to perforate the well casing. Specifically, the reader device and the perforating tool can be transported together through the well casing past the identification devices. In addition, the reader device can be programmed to transmit the
25 control signal to detonate the perforating tool, upon reception of a response signal from an identification device located at a predetermined depth or location within the well. Stated differently, the reader device can be programmed to control the perforating tool responsive to locating a specific identification
30 device.

As other examples, the reader device can be configured to control setting tools for packers, bridge plugs or casing patches, to control instrument readings from logging tools, and to control jet cutters and similar tools. With the method of the invention
35 the true depth of the process tool can be ascertained in real time by the reader device using response signals from the identification devices. Accordingly, there is no need to ascertain the depth of the tool using an odometer, and expensive wire

logging techniques. In addition, operator computational errors are reduced because true depth readings can be provided without the requirement of additional computations. Further, for some processes, there is no need to transmit signals to the surface, as
5 the reader device can be programmed to control the process in situ within the well.

However, it is to be understood that the method of the invention can also be practiced by transmission of the control signals from the reader device to a controller or computer at the
10 surface, and control of the process tool by the controller or computer. In addition, control of the process tool can be performed dynamically as the process tool moves through the well with the reader device, or statically by stopping the process tool at a required depth. Further, the method of the invention can
15 be used to control a multi stage process, or to control a tool configured to perform multiple processes. For example, a combination packer setting and perforating tool can be configured to perform packer setting and perforating processes, as a function of true depth readings obtained using the method of the
20 invention.

In the illustrative embodiment the system includes the identification devices installed in casing collars at spaced intervals along the well casing. The identification devices include a programmable element, such as a transceiver chip for
25 receiving and storing identification information, such as casing collar and depth designations. Each identification device can be configured as a passive device, an active device having an antenna, or a passive device which can be placed in an active state by transmission of signals through well fluids.

30 The system also includes the reader device and the process tool configured for transport through the well casing. In addition to the transmitter and receiver, the reader device includes one or more programmable memory devices, such as semiconductor chips configured to receive and store information. The reader device
35 also includes a power source such as a power line to the surface, or a battery. In addition, the reader device includes a telemetry circuit for transmitting the control signals, which can be used to control the process tool, and to provide depth and other

information to operators and equipment at the surface. The system can also include a computer configured to receive and process the control signals, and to provide and store information in visual or other form for well operators and equipment. Further, the system can include a controller configured to process the control signals for controlling the process tool and various process equipment. The controller can be located at the surface, or on the process tool, to provide a self contained system. Also, the system can be transported to a well site in the form of a kit, and then assembled at the well site.

Brief Description of the Drawings

Figure 1 is a schematic diagram of a prior art downhole operation being performed using well logs and odometer readings from a tool positioning mechanism;

Figure 2 is a flow diagram illustrating steps in the method of the invention for controlling a perforating process in a well;

Figures 3A and 3B are schematic cross sectional views illustrating a system constructed in accordance with the invention for performing the perforating process;

Figure 3C is an enlarged portion of Figure 3B, taken along section line 3C, illustrating a perforating tool of the system;

Figure 3D is an enlarged portion of Figure 3A, taken along section line 3D, illustrating a reader device and an identification device of the system;

Figure 3E is an enlarged cross sectional view taken along section line 3E of Figure 3D illustrating a portion of the reader device;

Figure 3F is a side elevation view of an alternate embodiment active reader device and threaded mounting device;

Figure 4A is an electrical schematic for the system;

Figure 4B is a view of a computer screen for a computer of the system;

Figures 5A and 5B are schematic views illustrating exemplary spacer elements for spacing the reader device of the system from the perforating tool of the system;

Figures 6A-6D are schematic cross sectional views illustrating various alternate embodiment transport mechanisms for the system;

Figures 7A and 7B are schematic cross sectional views illustrating an alternate embodiment system constructed in accordance with the invention for performing a packer setting process in a well;

Figure 7C is an enlarged portion of Figure 7A taken along section line 7C illustrating a threaded connection of a tubing string of the alternate embodiment system; and

Figure 8A-8C are schematic cross sectional views illustrating an alternate embodiment multi stage method and system of the invention for performing a packer setting and a perforating processes in combination.

15

Detailed Description of the Preferred Embodiment

Referring to Figure 2, broad steps in a method for controlling an operation or process in a subterranean well in accordance with the invention are illustrated. The method, broadly stated, includes the steps of:

- A. Providing a process tool.
- B. Providing a reader device in signal communication with the process tool.
- C. Providing a transport mechanism for the process tool and the reader device.
- D. Providing spaced identification devices in a well casing readable by the reader device.
- E. Uniquely identifying each identification device and determining its depth, or location, in the well using well logs.
- F. Programming the reader device to transmit a control signal to the process tool upon reception of a response signal from a selected identification device.
- G. Transporting the process tool and the reader device through the well casing.
- H. Reading the identification devices using the reader device.

I. Transmitting the control signal to the process tool upon reception of the signal from the selected identification device to actuate the process tool at a selected depth.

Referring to Figures 3A-3D, a system 50 constructed in accordance with the invention is illustrated. The system 50 is installed in a subterranean well 52, such as an oil and gas production well. In this embodiment the system 50 is configured to perform a perforating process in the well 52. The perforating process performed in accordance with the invention provides an improved well 52, and improves production from the well 52.

The well 52 includes a well bore 54, and a well casing 56 within the well bore 54 surrounded by concrete 56. The well 52 extends from an earthen surface 60 through geological formations within the earth, which are represented as Zones E, F and G. The earthen surface 60 can be the ground, or alternately a structure, such as an oil platform located above water. In the illustrative embodiment, the well 52 extends generally vertically from the surface 60 through Zones E, F, and G. However, it is to be understood that the method can also be practiced on inclined wells, and on horizontal wells.

The well casing 56 comprises a plurality of tubular elements 62, such as lengths of metal pipe or tubing, connected to one another by collars 64. The casing 56 includes an inside diameter adapted to transmit fluids into, or out of, the well 52, and an outside diameter surrounded by the concrete 58. The collars 64 can comprise couplings having female threads adapted for mating engagement with male threads on the tubular elements 62. Alternately, the collars 64 can comprise weldable couplings adapted for welding to the tubular elements 62.

Also in the illustrative embodiment the casing 56 is illustrated as having the same outside diameter and inside diameter throughout its length. However, it is to be understood that the casing 56 can vary in size at different depths in the well 52, as would occur by assembling tubulars with different diameters. For example, the casing 56 can comprise a telescoping structure in which the size thereof decreases with increasing depth.

Based on an open hole well log (36-Figure 1), or other information, it is determined that Zone F of the well 52 may contain oil and gas. It is thus desired to perforate the casing 56 proximate to Zone F to establish fluid communication between
5 Zone F, and the inside diameter of the well casing 56.

For performing the perforating process, the system 50 includes a perforating tool 68, and a reader device 70 in signal communication with the perforating tool 68. The system 50 also includes a plurality of identification devices 72 (Figure 3D)
10 attached to the collars 64 on the casing 56, and readable by the reader device 70. In addition, the system 50 includes a transport mechanism 66W for transporting the perforating tool 68 and the reader device 70 through the well casing 56 to Zone F. If desired, the system 50 can be transported to the well 52 as a kit, and then
15 assembled at the well 52.

As shown in Figure 3C, the perforating tool 68 includes a detonator 74 (illustrated schematically) and a detonator cord 76 in signal communication with the detonator 74. The detonator 74 can comprise a commercially available impact or electrical
20 detonator configured for actuation by a signal from the reader device 70. Similarly, the detonator cord 76 can comprise a commercially available component. The detonator 74 and the detonator cord 76 are configured to generate and apply a threshold detonating energy to initiate a detonation sequence of
25 the perforating tool 68. In the illustrative embodiment, the detonator 74 is located on, or within, the perforating tool 68.

As shown in Figure 3C, the perforating tool 68 also includes one or more charge carriers 78 each of which comprises a plurality of charge assemblies 80. The charge carriers 78 and
30 charge assemblies 80 can be similar to, or constructed from, commercially available perforating guns. Upon detonation, each charge assembly 80 is adapted to blast an opening 82 through the casing 56 and the concrete 58, and into the rock or other material that forms Zone F.

35 As shown in Figure 3D, each collar 64 includes an identification device 72. Each identification device 72 can be attached to a resilient o-ring 86 placed in a groove 84 within each collar 64.

In the illustrative embodiment, the identification devices 72 comprise passive radio identification devices (PRIDs). PRIDs are commercially available and are widely used in applications such as to identify merchandise in retail stores, and books in libraries. The PRIDs include a circuit which is configured to resonate upon reception of radio frequency energy from a radio transmission of appropriate frequency and strength. Passive PRIDs do not require a power source, as the energy received from the transmission signal provides the power for the PRIDs to transmit a reply signal during reception of the transmission signal.

The identification device 72 includes an integrated circuit chip, such as a transceiver chip, having memory storage capabilities. The integrated circuit chip can be configured to receive RF signals and to encode and store data based on the signals. During a data encoding operation each identification device 72 can be uniquely identified such that each collar 64 is also uniquely identified. This identification information is indicated by the C1-C8 designations in Figures 3A and 3B. In addition, the depth of each collar 64 can be ascertained using well logs, as previously explained and shown in Figure 1. The depth information can then be correlated to the identification information encoded into the identification device 72. A record can thus be established identifying each collar 64 and its true depth in the well 52.

Alternately, as shown in Figure 3F, identification device 72A can be in the form of an active device having a separate power source such as a battery. In addition, the identification device 72A can include an antenna 89 for transmitting signals. Alternately, an identification device (not shown) can be configured to transmit signals through a well fluid or other transmission medium within the well 52. Such an identification device is further described in previously cited parent application serial no. 09/286,650, which is incorporated herein by reference.

As also shown in Figure 3F, the identification device 72A can be contained in a threaded mounting device 87. The threaded mounting device 87 can comprise a rigid, non-conductive material such as a plastic. The threaded mounting device 87 is configured

to be screwed into the middle portions of the casing collar 64 (Figure 3D), and to be retained between adjacent tubular elements of the casing 56. The threaded mounting device 87 includes a circumferential groove 91 for the antenna 89, and a recess 93 for the identification device 72A. If desired, the antenna 89 and the identification device 72A can be retained in the groove 91 and the recess 93 using an adhesive or a suitable fastener.

Referring to Figure 3E, the reader device 70 is shown in greater detail. The reader device 70 is configured to transmit RF transmission signals at a selected frequency to the identification devices 72, and to receive RF response signals from the identification devices 72. As such, the reader device 70 includes a base member 77 having a transmitter 73 configured to transmit transmission signals of a first frequency to the identification devices 72. The reader device 70 includes a receiver 71 on the base member 77 configured to receive signals of a second frequency from the identification devices 72.

Preferably, the transmitter 73 is configured to provide relatively weak transmission signals such that only an identification device 72 within a close proximity (e.g., one foot) of the reader device 70 receives the transmission signals. Alternately, the antenna of the reader device 70 can be configured to provide highly directional transmission signals such that the transmission signals radiate essentially horizontally from the reader device 70. Accordingly, the transmission signals from the reader device 70 are only received by a single identification device 72 as the reader device passes in close proximity to the single identification device 72.

In addition to the transmitter 73 and the receiver 71, the reader device 70 includes a cover 79 made of an electrically non-conductive material, such as plastic or fiberglass. The reader device 70 also includes o-rings 75 on the base member 77 for sealing the cover 79, and a cap member 81 attached to the base member 77 which secures the cover 79 on the base member 77. In addition, the reader device 70 includes spacer elements 83 formed of an electrically non-conductive material such as ferrite, ceramic or plastic, which separate the transmitter 73 and the receiver 71 from the base member 77. In the illustrative

embodiment, the base member 77 is generally cylindrical in shape, and the spacer elements 83 comprise donuts with a half moon or contoured cross section.

Referring to Figure 4A, an electrical schematic for the system 50 is illustrated. As illustrated schematically, each identification device 72 includes a memory device 110, in the form of a programmable integrated circuit chip, such as a transceiver chip, configured to receive and store identification information. As previously explained, the identification information can uniquely identify each casing collar 64 with an alpha numerical, numerical or other designator. In addition, using previously prepared well logs, the depth of each uniquely identified casing collar 64 can be ascertained.

As also shown in Figure 4A, the reader device 70 includes the transmitter 73 for transmitting transmission signals to the identification devices 72, and the receiver 71 for receiving the response signals from the identification devices 72. The reader device 70 can be powered by a suitable power source, such as a battery, or a power supply at the surface. In addition, the reader device 70 includes a memory device 112, such as one or more integrated circuit chips, configured to receive and store programming information. The reader device 70 also includes a telemetry circuit 114 configured to transmit control signals in digital or other form, through software 116 to a controller 118, or alternately to a computer 122.

As is apparent the software 116 can be included in the controller 118, or in the computer 122. In addition, the computer 122 can comprise a portable device such as a lap top which can be pre-programmed and transported to the well site. Also, as will be further explained, the computer 122 can include a visual display for displaying information received from the reader device 70. The controller 118, or the computer 122, interface with tool control circuitry 120, which is configured to control the perforating tool 68 as required.

In the illustrative embodiment, the tool control circuitry 120 is in signal communication with the detonator 74 (Figure 3C) of the perforating tool 68. The tool control circuitry 120 can be located on the perforating tool 68, on the reader device 70, or at

the surface. The reader device 70 is programmed to transmit control signals to the tool control circuitry 120, as a function of response signals received from the identification devices 72. For example, in the perforating process illustrated in Figures 3A and 3B, coupling C4 is located proximate to the upper level, or entry point into Zone F. Since it is desired to actuate the perforating tool 68 while it is in Zone F, the reader device 70 can be programmed to transmit actuation control signals through the tool control circuitry 120 to the detonator 74 (Figure 3C), when it passes coupling C4 and receives response signals from the identification device 72 contained in coupling C4. Because coupling C4 is uniquely identified by the identification device 72 contained therein, and the depth of coupling C4 has been previously identified using well logs, the perforating process can be initiated in real time, as the perforating tool 68 passes coupling C4 and enters the section of the well casing 56 proximate to Zone F.

However, in order to insure that the detonation sequence is initiated at the right time additional factors must be considered. For example, the perforating tool 68 and reader device 70 can be transported through the well casing 56 with a certain velocity (V). In addition, the reader device 70 requires a certain time period (T1) to transmit transmission signals to the identification device 72 in coupling C4, and to receive response signals from the identification device 72 in coupling C4. In addition, a certain time period (T2) is required for transmitting signals to the tool control circuitry 120 and to the detonator 74 (Figure 3C). Further, the charge assemblies 80 require a certain time period (T3) before detonation, explosion and perforation of the casing 56 occur. All of these factors can be considered in determining which identification device 72 in which casing 64 will be used to make the reader device 70 transmit actuation control signals through the tool control circuitry 120 to the detonator 74 (Figure 3C).

In order to provide proper timing for the detonation sequence, the velocity (V) of the perforating tool 68 and the reader device 70 can be selected as required. In addition, as shown in Figures 5A and 5B, a spacer element 88 can be used to

space the perforating tool 68 from the reader device 70 by a predetermined distance (D). As shown in Figure 5A, the perforating tool 68 can be above the reader device 70 (i.e., closer to the surface 60), or alternately as shown in Figure 5B can be
5 below the reader device 70 (i.e., farther from the surface 60).

As an alternative to a dynamic detonation sequence, the perforating tool 68 can be stopped when the required depth is reached, and a static detonation sequence performed. For example, the reader device 70 can be programmed to send a signal
10 for stopping the perforating tool 68 when it reaches coupling C6. In this case, the signal from the reader device 70 can be used to control the wire line unit 92 and stop the wire line 90. The detonation and explosive sequence can then be initiated by signals from the tool control circuit 120, with the perforating tool 68 in
15 a static condition at the required depth.

As shown in Figure 4B, signals from the reader device 70 can be used to generate a visual display 124, such as a computer screen on the computer 122, which is viewable by an operator at the surface. The visual display 124 is titled "True Depth
20 Systems" and includes a power switch for enabling power to the reader device 70 and other system components. The visual display 124 also includes a "Depth Meter" that indicates the depth of the reader device 70 (or the perforating tool 68) within the well 52. The visual display 124 also includes "Alarm Indicators"
25 including a "Well Alarm Top" indicator, a "Well Alarm Bottom" indicator, and an "Explosive Device" indicator. The "Alarm Indicators" are similar to stop lights with green, yellow and red lights to indicate varying conditions.

The visual display 124 also includes "Power Indicators"
30 including a "True Depth Reader" power indicator, a "True Depth Encoder" power indicator, and a "System Monitor" power indicator. In addition, the visual display 124 includes various "Digital Indicators". For example, a "Line Speed" digital indicator indicates the speed at which the reader device 70, and the
35 perforating tool 68, are being transported through the well casing 56. An "Encoder Depth" digital indicator indicates the depth of each identification device 72 as the reader device 70 passes by the identification devices 72. A "True Depth" indicator indicates

the actual depth of the reader device 70 in real time as it is transported through the well casing 56.

The visual display 124 also includes a "TDS ID" indicator that indicates an ID number for each identification device 72. In addition, the visual display 124 includes a "TDS Description" indicator that further describes each identification device 72 (e.g., location in a specific component or zone). The visual display 124 also includes a "Time" indicator that can be used as a time drive (forward or backward) for demonstration or review purposes. Finally, the visual display 124 includes an "API Log" which indicates log information, such as gamma ray or SPE readings, from the previously described well logs, correlated to the "Digital Indicators" for depth.

Referring again to Figures 3A and 3B, in the embodiment illustrated therein, the transport mechanism 66W includes a wire line 90 operable by a wire line unit 92, substantially as previously explained and shown in Figure 1. The wire line 90 can comprise a slick line, an electric line, a braided line, or coil tubing. If the controller 118, or the computer 122, is located at the surface 60, the wire line 90 can be used to establish signal communication between the reader device 70 and the controller 118 or the computer 122.

Referring to Figures 6A-6D, alternate embodiment transport mechanisms for transporting the perforating tool 68 and the reader device 70 through the casing 56 are shown. In Figure 6A, a transport mechanism 66P comprises a pump for pumping a conveyance fluid through the inside diameter of the casing 56. The pumped conveyance fluid then transports the perforating tool 68 and the reader device 70 through the casing 56. In Figure 6B, a transport mechanism 66R comprises one or more robotic devices attached to the perforating tool 68 and the reader device 70, and configured to transport the perforating tool 68 and the reader device 70 through the casing 56. In Figure 6C, a transport mechanism 66G comprises gravity (G) such that the perforating tool 68 and the reader device 70 free fall through the casing 56. The free fall can be through a well fluid within the casing 56, or through air in the casing 56. In Figure 6D, a transport mechanism 66PA includes a parachute which controls the rate of descent of

the perforating tool 68 and the reader device 70 in the casing 56. Again, the parachute can operate in a well fluid, or in air contained in the casing 56.

Referring to Figures 7A-7C, an alternate embodiment system 50A constructed in accordance with the invention is illustrated. The system 50A is installed in a subterranean well 52A, such as an oil and gas production well. In this embodiment the system 50A is configured to perform a packer setting process in the well 52A.

10 The well 52A includes a well bore 54A, and a well casing 56A within the well bore 54A surrounded by concrete 58A. The well casing 56A comprises a plurality of tubular elements 62A, such as lengths of metal pipe or tubing, connected to one another by collars 64A. The well 52A extends from an earthen surface 15 60A through geological formations within the earth, which are represented as Zones H and I.

For performing the packer setting process, the system 50A includes a packer setting tool 68A, an inflation device 98A for the packer setting tool 68A, and a reader device 70A in signal 20 communication with the packer setting tool 68A. In this embodiment, the inflation device 98A is located on the surface 60A such that a wire, or other signal transmission medium must be provided between the packer setting tool 68A and the inflation device 98A. The packer setting tool 68A can include an 25 inflatable packer element designed for inflation by the inflation device 98A and configured to sealingly engage the inside diameter of the casing 56A. In Figure 7B, the inflatable packer element of the packer setting tool 68A has been inflated to seal the inside diameter of the casing 56A proximate to Zone I.

30 The system 50A also includes a plurality of identification devices 72 (Figure 3D) attached to the collars 64A on the casing 56A, and readable by the reader device 70A. In addition, the system 50A includes a transport mechanism 66A for transporting the packer setting tool 68A and the reader device 70A through the 35 well casing 56A to Zone I. In this embodiment, the transport mechanism 66A comprises a tubing string formed by tubular elements 102A. As shown in Figure 7C, each tubular element 102A includes a male tool joint 94A on one end, and a female tool

joint 96A on an opposing end. This permits the tubular elements 102A to be attached to one another to form the transport mechanism 66A. In addition, the packer setting tool 68A can include a central mandrel in fluid communication with the inside
5 diameter of the transport mechanism 66A.

The reader device 70A is programmed to transmit a control signal to the inflation device 98A upon actuation by a selected identification device 72 (Figure 3D). For example, in the packer setting process illustrated in Figures 7A and 7B, coupling C4A is
10 located proximate to the upper level, or entry point into Zone I. Since it is desired to inflate the inflatable packer element of the packer setting tool 68A while it is proximate to Zone I, the reader device 70A can be programmed to transmit the control signal to the inflation device 68A when it reaches coupling C4A. In this
15 embodiment a spacer element 88A separates the packer setting tool 68A and the reader device 70A. In addition, the packer setting tool 68A is located downhole relative to the reader device 70A.

In order to insure that the packer setting sequence is
20 initiated at the right time additional factors must be considered as previously explained. These factors can include the velocity (V) of the packer setting tool 68A and the reader device 70A, and the time required to inflate the inflatable packer element of the packer setting tool 68A. Alternately, the packer setting tool 68A
25 can be stopped at a particular coupling (e.g., coupling C5A) and then inflated as required. In this case the reader device 70A can be programmed to transmit the control signals to the visual display 124 (Figure 4B) on the surface 60A when the packer tool 68A passes a coupling 64A at the required depth. The operator
30 can then control the inflation device 98A to initiate inflation of the packer setting tool 68A. Alternately the inflation sequence can be initiated automatically by the tool control circuit 120 (Figure 4A).

In each of the described processes the method of the
35 invention provides an improved well. For example, in the perforating process of Figures 3A and 3B, the well 52 can be perforated in the selected zone, or in a selected interval of the selected zone. Production from the well 52 is thus optimized and

the well 52 is able to produce more fluids, particularly oil and gas.

Referring to Figures 8A-8C, a multi stage operation performed in accordance with the method of the invention is illustrated. Initially, as shown in Figure 8A, a combination tool 130 is provided. The combination tool 134 includes a packer setting tool 132 and a perforating tool 134, which function substantially as previously described for the packer setting tool 68A (Figure 7B), and the perforating tool 68 (Figure 3A) previously described. In addition, the combination tool 134 includes the reader device 70 and the casing 56 includes identification devices 72 (Figure 3D) substantially as previously described. As also shown in Figure 8A, the combination tool 130 is transported through the casing 56 using the gravity transport mechanism 66G. Alternately, any of the other previously described transport mechanisms can be employed.

Next, as shown in Figure 8B, the packer setting tool 132 is actuated such that an inflatable packer element of the tool 132 seals the casing 56 at a desired depth. In this embodiment the packer setting tool 132 is a self contained unit, with an integral inflation source. As with the previously described embodiments, the reader device 70 provides control signals for controlling the packer setting tool 132, and the packer setting process. For example, the inflatable packer element of the packer setting tool 132 can be inflated when the reader device 70 passes a selected coupling 64, and receives a response signal from the identification device 72 contained within the selected coupling 64. As also shown in Figure 8B, the perforating tool 134 separates from the packer setting tool 132 and continues to free fall through the casing 56.

Next, as shown in Figure 8C, the perforating tool 132 is controlled such that detonation and explosive sequences are initiated substantially as previously described. Again the reader device 70 provides control signals, for controlling the perforating tool 132 to initiate the detonation and explosive sequences at the proper depth. As indicated by the dashed arrows in Figure 8C explosion of the charge assemblies 80 (Figure 3C) of the

perforating tool 134 forms openings in the casing 58 and the concrete 58.

Thus the invention provides a method and a system for performing various operations or processes in wells and for
5 improving production from the wells. While the invention has been described with reference to certain preferred embodiments, as will be apparent to those skilled in the art, certain changes and modifications can be made without departing from the scope of the invention as defined by the following claims.

WHAT IS CLAIMED IS:

1. A method for performing an operation in a well comprising:
 - 5 providing a first device in the well which is uniquely identified and located at a known depth in the well;
 - providing a second device configured to locate the first device in the well;
 - transporting the second device through the well; and
 - 10 controlling the operation responsive to the second device locating the first device.
2. The method of claim 1 further comprising transporting a process tool through the well with the second device and
15 controlling the process tool responsive to the second device locating the first device.
3. The method of claim 1 wherein the first device comprises a radio identification device.
20
4. The method of claim 1 wherein the second device comprises a radio frequency transmitter configured to provide a transmission signal for reception by the first device and a receiver configured to receive a response signal from the first
25 device.
5. The method of claim 1 wherein the operation comprises a process selected from the group consisting of perforating processes, packer setting processes, bridge plug setting
30 processes, logging processes, inspection processes, chemical treating processes, casing patch processes, jet cutting processes and cleaning processes.
6. A method for performing an operation in a well
35 comprising:
 - providing a first device at a known depth in the well configured to transmit a signal which identifies the first device;

- providing a second device configured to receive the signal and to control the operation upon reception of the signal;
transporting the second device through the well proximate to the first device; and
5 controlling the operation responsive to reception of the signal by the second device.

7. The method of claim 6 wherein the second device comprises a receiver for receiving the signal and a transmitter
10 for transmitting a second signal to the first device.

8. The method of claim 7 further comprising transporting a process tool through the well with the second device and controlling the process tool using the signal to perform the
15 operation.

9. The method of claim 8 wherein the process tool comprises a perforating tool and the signal initiates a perforating process using the perforating tool.
20

10. The method of claim 8 wherein the process tool comprises a packer setting tool and the signal initiates setting of a packer element using the packer setting tool.

25 11. A method for performing an operation in a well comprising:

- providing a process tool;
- providing a plurality of spaced, uniquely identified identification devices in the well;
- 30 providing a reader device configured to read the identification devices and to transmit a control signal for controlling the process tool;
- programming the reader device to transmit the control signal at a selected identification device;
- 35 transporting the process tool and the reader device through the well;
- reading the identification devices using the reader tool; and

transmitting the control signal at the selected identification device to control the process tool and perform the operation.

5 12. The method of claim 11 wherein the process tool comprises a perforating tool configured to form openings in the well.

10 13. The method of claim 11 wherein the process tool comprises a packer tool configured to seal a portion of the well.

15 14. The method of claim 11 wherein the process tool comprises a combination tool configured to perform multiple operations in the well.

15 15. The method of claim 11 wherein the transporting step is performed using a transport mechanism selected from the group consisting of wire lines, pumps, blowers, parachutes, coil tubing and tubing strings.

20 16. The method of claim 11 wherein the transporting step is performed by gravity.

25 17. The method of claim 11 wherein the operation comprises a process selected from the group consisting of perforating processes, packer setting processes, bridge plug setting processes, logging processes, inspection processes, chemical treating processes, casing patch processes, jet cutting processes and cleaning processes

30 18. A method for performing an operation in a well comprising:

35 providing a well casing comprising a plurality of radio identification devices located at spaced intervals along a length thereof;

 determining a depth of each radio identification device within the well;

providing a process tool configured to perform the operation at a selected portion of the well casing proximate to a selected radio identification device;

5 providing a reader device configured to identify each radio identification device;

moving the process tool and the reader device through the well casing; and

10 controlling the process tool to perform the operation at the selected portion when the reader device is proximate to the selected radio identification device.

19. The method of claim 18 wherein the determining step comprises logging the well to provide a well log and ascertaining the depth using the well log.

15 20. The method of claim 18 further comprising establishing a record of the well using information from the determining step.

21. The method of claim 18 wherein the controlling step is performed dynamically as the process tool moves through the well casing.

22. The method of claim 18 wherein the controlling step is performed statically by stopping the process tool proximate to the selected radio identification device.

23. The method of claim 18 wherein the moving step is performed using gravity or a transport mechanism.

30 24. A method for performing a perforating operation in a well comprising:

providing a well casing comprising a plurality of couplings;

placing a plurality of radio identification devices in the couplings configured to transmit rf signals;

35 providing a perforating tool configured to form an opening in a selected portion of the well casing;

providing a reader device configured to receive the rf signals from the radio identification devices and to control the perforating tool responsive to the rf signals;

5 transporting the perforating tool and the reader device through the well casing; and
controlling the perforating tool using the reader device to form the opening.

10 25. The method of claim 24 further comprising spacing the perforating tool from the reader device by a selected distance.

26. The method of claim 24 further comprising detonating the perforating tool responsive to a control signal from the reader device.

15 27. The method of claim 24 further comprising detonating the perforating tool during the transporting step.

20 28. The method of claim 24 wherein the transporting step is performed using a transport mechanism.

29. The method of claim 24 wherein the transporting step is performed by free falling the perforating tool and the reader device through the well casing.

25 30. A method for performing a setting operation in a well comprising:

providing a well casing comprising a plurality of couplings;
placing a plurality of radio identification devices in the
30 couplings configured to transmit rf signals;

providing a setting tool configured to seal a selected portion of the well casing;

providing a reader device configured to receive the rf signals from the radio identification devices and to control the
35 setting tool responsive to the rf signals;

transporting the setting tool and the reader device through the well casing; and

controlling the setting tool using the reader device.

31. The method of claim 30 further comprising spacing the setting tool from the reader device by a selected distance.

5 32. The method of claim 30 wherein the setting tool comprises a packer setting tool comprising an inflatable packer element.

10 33. The method of claim 30 wherein the transporting step is performed using a transport mechanism.

15 34. The method of claim 30 wherein the transporting step is performed by free falling the setting tool and the reader device through the well casing.

35. The method of claim 30 wherein the setting tool comprises a bridge plug setting tool.

20 36. A method for performing a first operation and a second operation in a well comprising:

 providing a plurality of uniquely identified identification devices located at spaced intervals at known depths within the well;

25 providing a first process tool configured to perform the first operation;

 providing a second process tool configured to perform the second operation;

 providing a reader device configured to identify each identification device;

30 moving the first process tool and the second process tool with the reader device through the well;

 controlling the first process tool to perform the first operation when the reader device is proximate to a first identification device; and

35 controlling the second process tool to perform the second operation when the reader device is proximate to a second identification device.

37. The method of claim 36 wherein the first process tool and the second process tool are initially attached to one another and separated between the first identification device and the second identification device.

5

38. The method of claim 36 wherein the well comprises a well casing the identification devices comprise radio identification devices on the well casing.

10

39. The method of claim 36 wherein the reader device comprises a radio frequency transmitter configured to provide a transmission signal for reception by the identification devices and a receiver configured to receive response signals from the identification devices.

15

40. The method of claim 36 wherein the first operation comprises a packer setting process and the second operation comprises a perforating process.

20

41. The method of claim 36 wherein the first operation and the second operation comprise a process selected from the group consisting of perforating processes, packer setting processes, bridge plug setting processes, logging processes, inspection processes, chemical treating processes, casing patch processes, jet cutting processes and cleaning processes

25

42. A method for performing a setting operation and a perforating operation in a well comprising:

30 providing a setting tool configured to perform the setting operation and a perforating tool configured to perform the perforating operation;

providing a well casing comprising a plurality of radio identification devices located at known depths within the well;

35 providing a reader device configured to receive rf signals from the radio identification devices and to control the setting tool and the perforating tool responsive to the rf signals;

transporting the setting tool, the perforating tool and the reader device through the well casing;

controlling the setting tool to perform the setting operation when the reader device receives a first rf signal from a first radio identification device; and

controlling the perforating tool to perform the perforating operation when the reader device receives a second rf signal from a second radio identification device.

43. The method of claim 42 wherein the setting tool and the perforating tool are contained on a combination tool and are separated between the first radio identification device and the second radio identification device.

44. The method of claim 42 wherein the reader device is attached to the perforating tool during the transporting step.

45. A method for improving production in an oil or gas well comprising:

providing a first device at a known depth in the well configured to transmit a signal which identifies the first device; providing a second device configured to receive the signal and to control an operation within the well upon reception of the signal;

transporting the second device through the well proximate to the first device; and

controlling the operation responsive to reception of the signal by the second device.

46. The method of claim 45 wherein the second device comprises a receiver for receiving the signal and a transmitter for transmitting a second signal to the first device.

47. The method of claim 45 further comprising transporting a process tool through the well with the second device and controlling the process tool using the signal to perform the operation.

48. The method of claim 47 wherein the process tool comprises a perforating tool and the signal initiates a perforating process using the perforating tool.

5 49. The method of claim 47 wherein the process tool comprises a packer setting tool and the signal initiates setting of a packer element using the packer setting tool.

10 50. A method for improving production in an oil or gas well comprising:

 providing a well casing comprising a plurality of radio identification devices located at spaced intervals along a length thereof;

15 determining a depth of each radio identification device within the well;

 providing a process tool configured to perform an operation at a selected portion of the well casing proximate to a selected radio identification device;

20 providing a reader device configured to identify each radio identification device;

 moving the process tool and the reader device through the well casing; and

25 controlling the process tool to perform the operation at the selected portion when the reader device is proximate to the selected radio identification device.

30 51. The method of claim 50 wherein the determining step comprises logging the well to provide a well log and ascertaining the depth using the well log.

 52. The method of claim 50 further comprising establishing a record of the well using information from the determining step.

35 53. The method of claim 50 wherein the controlling step is performed dynamically as the process tool moves through the well casing.

54. The method of claim 50 wherein the controlling step is performed statically by stopping the process tool proximate to the selected radio identification device.

5 55. The method of claim 50 wherein the moving step is performed using gravity or a transport mechanism.

56. A system for performing an operation in a well comprising:

10 a process tool configured for transport through the well;
a plurality of radio identification devices located at spaced intervals at known depths in the well configured to transmit response signals for uniquely identifying each radio identification device; and

15 a reader device configured for transport through the well for receiving the response signals from the radio identification devices and for controlling the process tool responsive to the response signals.

20 57. The system of claim 56 wherein the reader device is attached to the process tool.

58. The system of claim 56 further comprising a transport mechanism configured to move the process tool and the reader
25 device through the well.

59. The system of claim 56 wherein the reader device comprises a receiver for receiving the response signals and a transmitter for transmitting transmission signals to the radio
30 identification devices.

60. The system of claim 56 wherein the process tool comprises a perforating tool and the control signal controls a perforating process.

35 61. The system of claim 56 wherein the process tool comprises a packer setting tool and the control signal controls setting of a packer element.

62. The system of claim 56 further comprising a computer in signal communication with the reader device comprising a visual display generated using signals from the reader device.

5

63. A system for performing an operation in a well comprising:
a well casing comprising a plurality of tubular elements joined by casing couplings;
10 a process tool configured for transport through the well casing;
a plurality of radio identification devices located on the couplings and configured to transmit response signals; and
15 a reader device attached to the process tool and configured to receive the response signals from the radio identification devices and to transmit control signals for controlling the process tool.

64. The system of claim 63 wherein the radio identification devices comprise radio identification devices.

65. The system of claim 63 wherein the reader device comprises a radio frequency transmitter configured to provide a transmission signal for reception by the radio identification devices and a receiver configured to receive the response signals.

66. The system of claim 63 wherein the process tool is configured for transport through the well casing by gravity.

30 67. The system of claim 63 further comprising a transport mechanism for transporting the process tool and the reader device through the well casing.

35 68. The system of claim 63 wherein the transport mechanism comprises a mechanism selected from the group consisting of wire lines, pumps, blowers, parachutes, coil tubing and tubing strings.

69. The system of claim 63 further comprising a computer in signal communication with the reader device comprising a visual display generated using the control signals.

- 5 70. A system for perforating a well casing comprising:
a perforating tool comprising a plurality of charge assemblies;
a plurality of radio identification devices attached to the well casing at spaced intervals at known depths in the well casing and configured to transmit rf signals;
10 a reader device attached to the perforating tool and configured to receive the rf signals from the radio identification devices and to control detonation of the charge assemblies responsive to the rf signals; and
15 a transport mechanism for transporting the perforating tool and the reader device through the well casing.


71. The system of claim 70 wherein the well casing comprises a plurality of collars and the radio identification devices are attached to the collars.
20

72. The system of claim 70 further comprising a detonator in signal communication with the reader device and configured to detonate the charge assemblies.
25

73. A system for setting a setting tool in a well casing comprising:
a plurality of radio identification devices attached to the well casing at spaced intervals and known depths and configured to transmit rf signals;
30 a reader device attached to the packer tool and configured to receive the rf signals from the radio identification devices and to control the setting tool responsive to the rf signals; and
a transporting mechanism for transporting the setting tool
35 and the reader device through the well casing.

74. The system of claim 73 wherein the well casing comprises a plurality of collars and the radio identification devices are attached to the collars.

- 5 75. The system of claim 73 wherein the setting tool comprises a packer setting tool.






FIGURE 2




FIGURE 3A




FIGURE 3B




FIGURE 3C




FIGURE 3D




FIGURE 3E




FIGURE 3F




FIGURE 4A




FIGURE 4B




FIGURE 5A




FIGURE 5B




FIGURE 6A




FIGURE 6B




FIGURE 6C




FIGURE 6D




FIGURE 7A

FIGURE 7B




FIGURE 7C




FIGURE 8A




FIGURE 8B




FIGURE 8C